

Mortise Locks MS Escutcheon Plates



(with Deadbolt)





FEATURES & OPTIONS

Door Thickness

1-3/4" standard; for doors over 1-3/4" specify door thickness

Backset

2-3/4" only

Lock Hand

Lock bodies are easily field reversible

Lock Case

Heavy duty wrought steel, zinc dichromate plated

Center to Center

3-7/8" (98mm)

Armor Faceplate

Stainless steel; 8"x1-7/32"; ANSI standard A115.1

Deadbolt

1" throw, hardened stainless steel

Latchbolt

3/4" throw, one-piece stainless steel with anti-friction reversible tongue

Auxiliary Latch

Stainless steel, non-handed

Strike

Stainless steel; curve lip with dust box; ANSI standard A115.1

Cylinder

6-pin SC "C" keyway solid brass cylinder standard Also available in: 5-pin SC keyway 5-pin KW keyway 6 or 7-pin SFIC

FINISHES

(other finishes available upon request with leadtime)

US26D - 626 - Satin Chrome

CODE COMPLIANCE

- Meets ANSI/BHMA A156.13. Series 4000, Grade 1
- Meets ADA Requirements
- UL 3-Hour Fire Rated

FUNCTIONS

- 1 Passage (F01)
- 4 Office/Entry (F04)
- 5 Classroom (F05)
- 7 Storeroom (F07)
- 9 Apartment Entrance Lock (F09)
- 13 Corridor Lock (F13)
- 14 Store/Utility Room Lock w/ Deadbolt (F14)
- 20 Entrance Lock (F20)
- 21 Dormitory/Bedroom (F21)
- 30 Institution Lock (F30)

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

LEVER OPTIONS

- EYT Lever
- EYM Lever
- EYH Lever
- EYR Lever



EYR - Lever

